

Night Vision Attachment AC-4222/4322



The AC-4222/4322 is an attachment for daytime weapon sights with 1x to 6x magnification that converts the sight into a high quality night vision weapon sight. The AC-4222/4322 mounts in front of a daytime sight. Re-zeroing is not required. The device allows the use of all the features of your favorite daytime sight during the night. The IR

illuminator could be mounted onto the optional Picatinny Rail. The AC-4222/4322 utilizes a Gen.2+ or Gen.3 Image Intensifier Tube. Transition from day to night shooting takes about 30 seconds without tools. The device has a built in automatic brightness control, which adjusts brightness to optimal level.

Features: Mounts in front of the day sight; no re-zeroing required; lightweight; waterproof; automatic bright light shut off and brightness control; multicoated optics; quick release mount

Standard accessories: Detachable IR illuminator; mounting rail; remote control; quick release mount; lens caps; light suppressors; hard waterproof case; batteries

Optional accessories: Sight mounting systems; weaver mount; platform ring; boresight attachment mount; long rail adaptor; OTIS lens swabs, lens cleaning kit, optics cleaning system

Specifications

Magnification	1x
Field of View	13°
IIT resolution, lp/mm	40 - 72
Lens system	F1.44, 80mm
Exit pupil, mm	21
Focus Range	10 m to infinity
Operational temperature	-40°C...+50°C
Battery	CR123
Battery Life, hours	60
Dimensions, mm	150x80x70
Weight, g	620