## EOTech 558 HWS

Holographic Weapon Sight by EOTech Models 558.A65





-0- RETICLE

The 558 is compatible with Gen-I-IIInight vision devices and features an adjustable, locking quick detach mount that offers instant removal. The operational buttons are located on the side of the sight making this optic ideal for use with EOTech switch-to-side magnifiers. The major advantage is extremely rapid reticle-on-target acquisition. Operators can quickly acquire the target and reticle in the same focal plane for fast and accurate shot placement. The sight can be used as a bright open reticle image or a fine dot which is limited only by the acuity of the shooter's eye. The heads-up display window allows an undistorted and unrestricted view of the target.

While in the NV mode, the sight is undetectable by night vision equipment. The HWS® can be positioned behind night vision systems without any "bloom" on the target area.

**Optional accessories:** Lens cleaning kit and OTIS lens swabs.

## 3476>>343

## **Specifications**

| FEATURE                    | SPECIFICATION                                      |
|----------------------------|--|
| Night Vision Compatibility | YES  |
| Magnification              | 1x   |
| Dimensions (L x W x H)     | 142.3 x55.9 x 73.7 mm                              |
| Weight                     | 391.2 g  |
| Optical Surfaces           | Anti-reflective coating on external surfaces       |
| Window Dimensions          | 30 x 23 mm   |
| Field of View              | 28 m @ 10 cm relief                                |
| Eye relief                 | Unlimited  |
| Brightness                 | 20 daylight settings (add. 10 settings for NV use) |
| Adjustment (per click)     | Approx 0.5 MOA (12.7mm at 91m) when zeroing        |
| Adjustment Range           | +/-40 MOA travel                                   |
| Reticle Option             | 0- 68 min ring and 1 MOA aiming dot                |
| Battery type               | Two 1.5 V AA batteries                             |
| Battery Life               |  |
| Lithium                    | 1000 hours at nominal setting 12 and room temp     |
| Alkaline                   | 600 hours at nominal setting 12 and room temp      |
| Mount                      | 1" Weaver or MIL-STD-1913 rail                     |
| Water Resistant            | Submersible to 10 m depth                          |
| Sealing                    | Internally fog-resistant optics                    |

<sup>\*</sup>Specifications are subject to change without notice. Images are for illustration purposes only.