EOTech XPS2 HWS

Holographic Weapon Sight by EOTech (Models XPS2-0, XPS2-0GRN, XPS2-1, XPS2-2, XPS2-300, XPS2-FN, XPS2-SA)



The EOTech XPS2 is the shortest, smallest and lightest EOTech model holographic weapon sight available without night vision. Its size and weight make it convenient for hunters and law enforcement officers to carry. It is also fast and runs on a single 123 battery. The compact, single-lithium-battery configuration leaves more rail space than ever for rear iron sights or magnifiers.

Achieve faster target acquisition with the new easy-to-see Green reticle that is approximately 6X easier to see than red in daytime. It has convenient side buttons to add a magnifier and features an adjustable, locking, quick-detach lever for easy attachment and removal.

Designed with tactical shooters in mind, the EOTech XPS2-300 offers a 2-dot ballistic drop reticle that allows the shooter to zero either subsonic or supersonic rounds in the same reticle pattern. Its size and weight make it convenient for hunters and law enforcement officers to carry.

This sight has the same body style as the XPS3™ model, but the EOTech XPS2 does not have night vision-compatibility.

Optional accessories: Lens cleaning kit and OTIS lens swabs.

CCOSAL STORY

Specifications

FEATURE	SPECIFICATION
Night Vision Compatibility	No
Magnification	1x
Dimensions (L x W x H)	97 x 54 x 64 mm
Weight	255 g
Optical Surfaces	Anti-reflective coating on external surfaces
Window Dimensions	30 x 23 mm
Field of View	28 m @ 8 cm relief
Eye relief	Unlimited
Adjustment (per click)	Approx 0.5 MOA (12.7mm at 91m) when zeroing
Adjustment Range	+/-40 MOA travel
Reticle Option	
XPS2-0, OGRN,	0- 68 min ring and 1 MOA aiming dot
XPS2-1	1- Single 1 MOA aiming dot (no outer circle)
XPS2-2	2- 68 min ring and (2) 1 MOA aiming dot
XPS2-300	2-dot reticle w/ .300 Blackout ballistics on hood
XPS2-FN	reticle pattern w/ FN less lethal reticle
XPS2-SA	reticle pattern w/ SAGE less lethal reticle
Battery type	One 123 lithium battery
Battery Life	600 hours at nominal setting 12 and room temp
Mount	1" Weaver or MIL-STD-1913 rail
Water Resistant	Submersible to 3 m depth
Sealing	Internally fog-resistant optics

^{*}Specifications are subject to change without notice. Images are for illustration purposes only.