



- Ambidextrous magnification throw levers
- Integrated Picatinny rail
- Improved battery cover
- Eye relief and bore sighting remain constant between magnifications
- Generous eye relief and wide viewing angle for rapid target acquisition
- hard-wearing CERAKOTE® performance finishes
- Large exit pupil diameter for extended low light performance
- Shock protected precision optics for rugged reliable performance
- Integrated lever-lock mount for optimum weight reduction
- Two sights in one
- Adjustable A.R.M.S. Lever (optional)

NEW ELCAN SpecterDR 1.5x/6x comes equipped with integrated Picatinny rails, ambidextrous magnification throw levers, improved battery covers, and hard-wearing CERAKOTE® performance finishes in Black or Flat Dark Earth (FDE).

The ELCAN SpecterDR 1.5x/6x is the second evolution in the family of Dual Role Optical Sights. Based upon the battle-proven SpecterDR design, the SpecterDR 1.5x/6x provides higher magnification to enable greater precision and longer engagement ranges, while at the same time providing exceptional field of view in CQB mode.

The SpecterDR 1.5-6 enjoys ELCAN's famous crystal-clear optics as well as a generous eye relief, making it the ideal instrument for designated marksman rifles and other long range applications. As with all SpecterDR sights, the magnification and field of view can be changed instantly with the throw of a lever. Depending upon the situation, the user may adjust the sight to illuminate the crosshair or just a brilliant red dot in the center. Because the reticles are etched in glass, they are plainly visible even in the case of loss of electrical power due to battery failure or EMP.

SPECIFICATIONS

Magnification (x)	6x / 1.5x
Reticle	Dual-thickness ballistic crosshair with user-selectable red dot and VSOR rangefinder
Aiming Dot diameter	1.5 MoA @ 6x, 6 MoA @ 1.5x
Ballistic correction:	
DFOV6-C10	CX5455 reticle: 100-1000m for 5.56 NATO
DFOV6-C20	CX5456 reticle: 100-1000m for 7.62 NATO
CQB offset	<44mm @ 60m
Field of View	16 deg @ 1x, 4 deg @ 4x
FoV @4x	7 m @ 100 m
FoV @1x	28.7 m @ 100 m
Illumination source	Battery-powered LED
Crosshair illumination	5 settings, night vision compatible
Red Dot illumination	5 settings, night vision compatible
Eye Relief	70 mm
Entrance pupil	42 mm
Exit pupil	7 mm
Nominal focus	300m @ 6x, 105m @ 1.5x
Fixed focus range	20m to infinity
Battery type	CR2032 (3v Lithium)
Battery life	382hrs on max RD/reticle setting 1730hrs on second highest RD setting 1208 hrs on second highest reticle setting
Exterior finish	CERAKOTE® performance finish in Black or FDE
Adjustment resolution	0.5 minute of angle
Adjustment range	120 minutes of angle
Base requirement	Mil-Std-1913 'Picatinny Rail'
Attachment	A.R.M.S. Levers
Shockproof	450 g's
Dimensions, mm	183 x 69 x 73 mm
Weight	715 g

Optional Accessories: XOPTTEK™ Micro Reflex Sight Hard Storage Case, Anti-Fog Lens Swabs; Anti-Fog Lens Cleaner; Lens Cleaning Kit