

Tangent Theta TT315P

3-15x50mm Professional Rifle Telescope

- 50mm objective lens
- 34mm main tube
- TOOL-LESS RE-ZERO® feature (US Patent # 10,591,253)
- eleven reticle illumination settings
- side parallax adjustment
- non-translating knobs with elevation zero-stop
- double-turn elevation with revolution and windage direction indicator
- 3-15x magnification range
- lockable rapid adjusting diopter



Tangent Theta 3-15x50mm model TT315P Rifle Telescope is a long-range precision sighting instrument for professional marksmen.

Designed for heavy field use, Tangent Theta's industry-leading development team has used their extensive experience to optimize and refine it for unfailing ruggedness, mechanical precision and unsurpassed image quality. Elevation and windage mechanisms exhibit precise tactile response and feature a truly TOOL-LESS RE-ZERO® procedure.

Tangent Theta rifle telescopes are built in Canada and are specifically designed and function-tested for long lifecycles in the harshest of environmental conditions.

Standard accessories: Set of Tenebraex flip covers; ARD, battery cap tool; lens tissue

Optional accessories: Hard storage case; lens cleaning kit

Specifications:

Magnification	3x-15x
Dimensions (L x W x H)	356 x 103 x 82mm
Weight	1025g
Tube diameter	34mm
Objective bell diameter	57mm
Objective lens diameter	50mm nominal
Eyepiece diameter	45mm
Reticle options	Gen 2, Gen 2XR, MoA, Gen 3XR
Field of View @ 3x	7.3 degrees (12.8m @ 100m)
Field of View @ 15x	1.6 degrees (2.8m @ 100m)
Diopter range	-3 to +2.5
Eye relief	90mm
Exit pupil @ 3x	11.5mm
Exit pupil @ 15x	3.5mm
Total Adjustment Range	
Elevation	34 mrad (117 MoA)
Windage	+/- 8 mrad (+/- 27 MoA)
Working Adjustment Range	
Elevation	28 mrad /96 MoA
Windage	+/- 6 mrad (+/- 20 MoA)
Adjustment resolution	0.1 mrad or 1/4 MoA
Re-zero mechanism	TOOL-LESS RE-ZERO® (patent pending)
Parallax adjustment range	50m to infinity
Crosshair illumination	LED, 11 settings
Battery type	DL2032 3v lithium
Exterior finish	Type II Anodized, matte
Environmental	
Waterproof	4 hours @ 10 meters
Shockproof	700g's @ 10,000 cycles
Standard accessories	Tenebraex® lens covers & ARD