

- Night Vision Compatible
- Magnifier Compatible
- Adjustable, locking quick-detach lever fits both 1" Weaver and MIL-STD-1913 rail
- Operates on 2 common AA Alkaline or Lithium batteries
- Easy adjust side buttons
- Reticle Options: 1-Dot Speed Ring and Ballistic reticle for .308 caliber




The Model 552™ is the most popular night vision-compatible holographic weapon sight available. Powered by globally available AA batteries, it's a favorite among professionals and enthusiasts alike.

The versatile mount fits both 1" Weaver and MIL-STD-1913 rails and comes equipped with a hex cross bolt and thumbscrew for secure, reliable installation. The heads-up display window allows an undistorted and unrestricted view of the target. Utilizing natural binocular vision is an advantage of this sighting system, as well as additional threat identification through increased operator situational awareness and peripheral vision.


The 552 can operate in tandem with Gen night vision intensifier tubes. While in the NV mode, the sight is undetectable by night vision equipment. The HWS® can be positioned behind night vision systems without any "bloom" on the target area.

1-Dot Speed Ring Reticle



The 68 MOA ring with 1 MOA dot is ideal for fast target acquisition. It provides three usable aiming points. The aiming points above were based on the following load: 223 Cal 62 Gr 2,900 Vel. Other loads and calibers can also be used, but the operator will have to establish the ranges associated with the aiming points. When using a shotgun, the 68 MOA ring can be used to represent shot patterns but will vary based on choke and shell selection.

XR308 Reticle



The XR308 reticle is specifically designed for the military M240 machine gun. It's calibrated for .308 Cal., 150 Gr. M59 FMJ rounds at approximately 2,800 fps from a 24.8" barrel.

Specifications:

Night Vision Compatibility	YES
Magnification	1x
Dimensions (L x W x H)	142.2 x 50.8 x 63.5 mm
Weight	326 g
Field of View	28 m @ 10 cm relief
Eye relief	Unlimited
Brightness	20 daylight settings 10 additional settings for Gen 1 through 3 night vision devices
Mount	1" Weaver or MIL-STD-1913 rail
Adjustment (per click)	Approx 0.5 MOA (12.7mm at 91m)
Reticle Option (552. A65)	68 min ring and 1 MOA aiming dot
Reticle Option (552. XR308)	XR308
Operating temperature	-40°C to 60°C
Battery type	Two 1.5 V AA batteries
Battery Life	Lithium 2500 continuous hours at nominal setting 12 at room temp Alkaline 2600 continuous hours at nominal setting 12 at room temp
Water Resistant	Submersible to 10 m depth
Sealing	Internally fog-resistant optics