

- Night Vision Compatible
- Magnifier Compatible
- Easy adjust side buttons
- 1" Weaver and MIL-STD-1913 rail
- Submersible to 10 m depth



The EXPS3 offers true 2-eyes-open shooting, and a 7 mm raised base that still allows for iron sight access. It features easy-to-adjust side buttons and an adjustable, locking, quick-detach lever for easy attachment and removal.

The EXPS3 can operate in tandem with Generation 1-3 night vision intensifier tubes. It is also the optic of choice for the technologically advanced modern rifle hunter. The night vision compatibility makes it a versatile choice for day or night hunting. It also provides the operator superior shooting performance, rapid reticle-on-target acquisition, full field of view and accurate shot placement.

The HWS® can be naturally employed by all levels of users, from novice to the most highly trained operator.

RETICLES



1-Dot Speed Ring Reticle - A 68 MOA ring with the top cutout and an easy-to-locate chevron at the bottom. Zero your .223/5.56 rifle at 50 yards and the DCR™ offers confident aiming points for up to 200 yards, with an additional 7-yard close-range solution at the chevron point.



1-Dot-Reticle - The 1 MOA dot-only reticle is ideal for users familiar with red dot sights, offering the simplicity of a single dot with the enhanced benefits of the HWS®.



2-Dot Speed Ring Reticle provides four usable aiming points. The aiming points are based on the following load: 223 Cal 62 Gr 2,900 Vel. Other loads and calibers can also be used, but the user will have to establish the ranges associated with the aiming points.



4-Dot Speed Ring Reticle is optimized for use with 5.56 NATO/.223 Cal. with 62 Gr. M855 FMJ rounds at approximately 2,680 fps from a 14.5" barrel. Note that the aiming dots may not be clearly distinguishable without Magnification.

SPECIFICATION

Night Vision Compatibility	YES
Magnification	1x
Field of View	28 m @ 8 cm relief
Eye relief	Unlimited
Windage & Elevation Adjustment	Approx 0.5 MOA per click
Brightness	20 daylight settings; 10 additional settings for night vision devices
Window Dimensions	30 x 23 mm
Reticle Option	
EXPS3-0 Black and Tan	1-Dot Speed Ring
EXPS3-1 Black and Tan	Single Dot Reticle
EXPS3-2 Black and Tan	2-Dot Speed Ring
EXPS3-4 Black	4-Dot Speed Ring
Battery type	One CR123 battery
Battery Life	1000 hours at room temp
Water Resistant	Submersible to 10 m depth
Operating Temperature	-40°C to +60°C
Mount	1" Weaver or MIL-STD - 1913 rail
Dimensions (L x W x H)	96.5 x 58.4 x 73.7 mm
Weight	317.5 g
Colour	Black, Tan